

# Product Specifications



**DIR-1G**  
**Smart Director, Generation 1**

## General Specifications

---

Brand	Director
Generation	1
Product Type	Director
Application	Provides unified management, control, and reporting on a cluster of Smart engines   Hosts open application framework
Includes	Operating system
LED Indicators	Hard drive activity   Network activity   Power   System overheat
Marketing Feature	Scales to cluster implementations up to 225,000 SF / 2000 fixtures
Mount Type	Rack
Package Quantity	1
Rack Type	EIA 19 in
Rack Units	1.0
Storage	Hard disk drive

## Dimensions

---

Depth	368.30 mm   14.50 in
Height	43.18 mm   1.70 in
Width	436.88 mm   17.20 in
Weight	6.58 kg   14.50 lb

## Mechanical Specifications

---

Communications Port Interface	RJ45 (2)   RJ45 IPMI (1)
Communications Ports, quantity	3
Serial Port Interface	PS/2 mouse (1)   RS•232 (1)   USB (2)
Serial Ports, quantity	5
Video Port Interface	VGA
Video Ports, quantity	1

## Electrical Specifications

---

ANSI/TIA Category	5e   6   6A
Input Voltage	100–240 Vac
Power Consumption, maximum	350 W
Power Frequency	50–60 Hz

## Environmental Specifications

---

Cooling	2 internal fans
Environmental Space	Indoor
Operating Humidity	8%–90%, non•condensing
Operating Temperature	+10 °C to +35 °C (+50 °F to +95 °F)
Storage Humidity	5%–95%, non•condensing

# Product Specifications

---



DIR-1G

Storage Temperature •40 °C to +70 °C (•40 °F to +158 °F)  
Safety Standard

## Regulatory Compliance/Certifications

---

**Agency**  
RoHS 2011/65/EU

**Classification**  
Compliant

